

Performance Verification of Health Monitoring System in 45 NM Technology Using Cadence Tool

Dr. H. Abdul Shabeer

Professor, Department of Electronics and Communication Engineering, Malla Reddy College of Engineering for Women, Hyderabad -500100, Telangana, India

Abstract- Due to the uncertain times such as this pandemic, it is important to keep trail of consumption. A certain number of people are disciplined on keeping a healthy diet whilst some of them are struggling and snacking more and not keeping up with a healthy diet. To check our body status, BMI (body mass index), BFP (Body Fat Percentage), BMD (Body Mineral Density), RMF (relative fat mass), BMR (basal metabolic rate) can be utilized as an indicator. Here we have analyzed BMI, BFP, BMD, RMF, BMR using elemental conditions like stature, weight, age, sexual inclination, abdomen circuit and so on. BMI can be used to screen for weight categories to check the health of an individual, BFP shows the fat in body, BMD exhibits minerals existing in body, RFM is viewed as obviously superior to BMI as it doesn't demonstrate about the fat mass, BMR shows the digestion pace. All the above-mentioned parameters are designed in Verilog language (RTL code) and it has been stimulated and physical design is carried out to get efficient analysis using Cadence tool.

Keywords: 45NM, VERILOG code, Physical Design, GDS 2, floorplan, power plan, routing, Cadence, Xilinx

1. INTRODUCTION

Prior to the origination of VLSI technology, most ICs had a restricted set of functions they could perform. Electronic circuits consist of a CPU, ROM, RAM and various glue logic. VLSI allows IC designers to add these onto the chip. Electronic fabrication units have leveled up, mostly due to the fast advances in large scale integration technologies and system design applications. With the advent of very large-scale integration (VLSI) designs, the number of applications of integrated circuits (ICs) in elevated-performance computing, controls, telecommunications, image & video processing, and consumer electronics has been evolving.

The present innovation in the technologies such as elevated resolution and low bit-rate video and mobile communications supplies the end-users a spectacular amount of applications, processing power. This trend is expected to grow rapidly, with very important implications on VLSI design and systems design.

2. LITERATURE SURVEY

BMI is utilized as valuable occupants level proportion of overweight and weight. It is common for both men and women respectively. The BMI pointer analyses & displays the range of body weight to the square of body height of a person. As indicated by the BMI value, individuals can tell whether they are under-weight, reasonable weight or over-weight. BMI has been normalized by age and sex to characterize hunger and stoutness.

BPF can be calculated using BMI. BFP of a person is the whole mass of fat cut-off by overall weight, duplicated by 100. Muscle versus fat includes necessary full & capacity body fat. RFM is approximation of weight in people that requires just calculation depending on the proportion of height and abdominal circumference estimations. Fat mass is known using two common approximations that is the height & waist circumference. BMI, RFM could be used in consistent clinical execution as an undeniable limit in assessing the body association.

3. METHODOLOGY

The methodology illustrates the flow of the code to be implemented. Comprehensively the flow chart is exhibited below where it explains various factors that are included in the code such as BMI, BMR, BMD, BFP, RMF, and how the formula is calculated and the code is designed.




Fig. 1: Flow Diagram Methodology

Here a variable "a" is used to establish the sexual orientation, when a=0, it is assumed female or, it can be regarded as male. The set input will be taken as 8-bit in which w[7:0] will be the weight of the body measured in kilograms, h[7:0] will be the height in centimetres, [7:0]age will be the given age of the person, waist[7:0]BFP is $((1.20 * BMI) + (0.23 * Age) - (10.8 * S) - 5.4)$, [7:0]RFM = (for male $64 - 20 \times (\text{tallness}/\text{abdomen circumference})$), for female $76 - 20 \times (\text{tallness}/\text{abdomen circumference})$ BMD is mapped out evidently from the weight approach of an established diagram. The final waveform of the Verilog code is obtained by using the Xilinx tool which simulates the code and gives the necessary result.




Fig 2: Flowchart of Verilog Code




Fig 3: Flowchart of Verilog Code




Fig 4: Simulated Waveform for The Verilog Code

```

cadence@usr16:digital
File Edit View Search Terminal Help
Warning : Possible timing problems have been detected in this design. [TIM-11]
          : The design is 'healthmonitor'.
          : Use 'report timing -lint' for more information.
@file(run.tcl) 30: report power > counter_power.rep
@file(run.tcl) 31: report area > counter_cell.rep
@file(run.tcl) 32: report gates > counter_gates.rep
#@ End verbose source run.tcl
WARNING: This version of the tool is 1194 days old.
@genus:root: 2> report power

=====
Generated by:      Genus(TM) Synthesis Solution 17.22-s017_1
Generated on:     Jul 08 2021 08:20:13 pm
Module:          healthmonitor
Operating conditions: slow
Interconnect mode: global
Area mode:       physical library
=====

Instance  Cells  Leakage  Dynamic  Total
          Cells Power(nW) Power(nW) Power(nW)
-----
healthmonitor  386   31.761 127089.816 127121.577

@genus:root: 3>

```




Fig 5: GUI Netlist

4. DESIGN OF HEALTH MOTITOR IN CADENCE PHYSICAL DESIGN FLOW

Physical design is the process of transforming a circuit explanation of the physical layout, which explains the position of cells and routes for the interconnections between the cells. The physical design contains many library & library exchange format files, Gate level netlist, synopsis design constraint file, Timing, Design rule violation. Clock design, technology files, Reports & scripts, GDS 2, CPF (Cadence Power Format) it is the power required to each gate will be defined, gates requiring same power.

FLOORPLAN: We estimate the die size to find the area required for the gate-level netlist to occupy. After the die size is evaluated, Pin Placement is done where input and output ports are connected with gates, later Macro Placement and Floor checkers are done.

POWERPLAN: It is the phase where we provide or supply power to each gate. Here higher metals are used for power planning because the area in higher metals is more which means the resistance is less.

This includes three steps:

- 1) Global Net Connections: Here we declare all voltage sources required for our design that is vdd & vss.

2) Mesh/Ring generations: In mesh, the top, bottom, left & right metal will be selected which generates stripes inside. In-ring analysis generates rings around the core of vdd & vss making stripes run through the core from where macros get power from.

3) Standard cell Routing: Provides power to the standard cell between the rows in the core area.




Fig 6: Power plan

ROUTING: It is the stage after Clock Tree Synthesis and optimization where the exact paths for the interconnection of standard cells and macros and input pins are determined. The connections using metals and vias are created in the layout, defined by the logical connections present in the netlist.




Fig 7: Routing

5. CONCLUSIONS

This paper presents verification of health monitoring system in 45 NM technology using cadence tool. The frontend and backend procedure along with the performance evaluation of the Verilog code and Physical design was carried out. The performance criteria were area and power analysis were checked after routing and optimized results were obtained, after this, the process was carried up to GDS 2. It was observed that the WNS (worst negative slack) was zero which meant no violations were present and the technology used was efficient. The area and power parameters were analyzed and we got an optimized result with improved efficiency.

REFERENCES

- [1] Adithi L1, Ranjith S2, Santhosh PV3, Deepthi KC “Implementation of Health Monitoring using Verilog” IRJET, Volume: 07 Issue: 06 June 2020
- [2] Smart health monitoring system using IoT based smart fitness mirror.
- [3] Internet of Thing Based Health Care Monitoring System, Shreyaasha Chaudhury, Debasmita Paul.
- [4] IOT Based Smart Health Monitoring Alert Device, K Hari Kishore, K.V.Surendra Nath, K V N Hari Krishna, D.Pavan Kumar, V.Manikanta, Fazal Noor Basha.
- [5] A Survey on Wearable Sensor-Based Systems for Health Monitoring and Prognosis Alexandros Pantelopoulos and Nikolaos G. Bourbakis.
- [6] Healthcare monitoring system based on IoT, Krishna C S, Nalini Sampath.
- [7] An IoT based Patient Health Monitoring System 1D. Shiva Rama Krishnan, 2Subhash Chand Gupta, 3Tanupriyam Choudhury.
